



# Ultra V Pro STPXXXS - C54/Nshb 410-430W

|                                       |     |
|---------------------------------------|-----|
| N                                     | 182 |
| 108 (6 × 18)                          |     |
| 1722 × 1134 × 30 (67.8 × 44.6 × 1.2 ) |     |
| 21.0 (46.3 )                          |     |
| 3.2 (0.126 )                          |     |
| 4.0                                   |     |
| (-)350 / (+)160                       |     |
| IP68 3                                |     |
| -40 °C - +85 °C                       |     |
| 1500 V DC (IEC)                       |     |
| MC4-EVO2                              |     |
| 25 A                                  |     |
| 0/+5 W                                |     |



|   |
|---|
| (Pmax/W)  |
| (Vmp/V)   |
| (Imp/A)   |
| (Voc/V)   |
| (Isc/A)   |
| (%)   |
| STC 1000W/m², 25 °C, AM=1.5; NIMDT: 800W/m², 20 °C, AM=1.5, 1 m/s Pmax +/- 3% |

|         |            |
|---------|------------|
| (NIMDT) | 42 ± 2 °C  |
| (Pmax)  | -0.29%/°C  |
| (Voc)   | -0.25%/°C  |
| (Isc)   | +0.046%/°C |

- & - 430W

