


STPXXXS - B72/Vnh

440-460W 21.1%



**

- CE
- IEC 61730
- IEC 61215
- SA 8000
- IEC TS 62941
- ISO 9001
- ISO 14001
- ISO 45001


2%





STPXXXS - B72/Vnh 440-460W

166
144 (6 × 24)
2095 × 1039 × 35 (82.5 × 40.9 × 1.4)
24.5 (54.0)
3.2 (0.126)
4.0 (-)350 / (+)160
STP-XC4
IP68 3
-40 ° C - +85 ° C
1500 V DC (IEC)
20 A
0/+5 W



	STP460S-B72/Vnh		STP455S-B72/Vnh		STP450S-B72/Vnh		STP445S-B72/Vnh		STP440S-B72/Vnh	
	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
(Pmax/W)	460	346.9	455	343.1	450	339.4	445	335.8	440	332.7
(Vmp/V)	41.8	38.5	41.6	38.4	41.4	38.2	41.2	38.0	41.0	37.8
(Imp/A)	11.01	9.00	10.94	8.94	10.87	8.89	10.81	8.84	10.74	8.78
(Voc/V)	49.6	46.5	49.4	46.3	49.2	46.2	49.0	46.0	48.8	45.8
(Isc/A)	11.74	9.47	11.67	9.42	11.61	9.37	11.54	9.31	11.47	9.25
%	21.1		20.9		20.7		20.4		20.2	

STC: 1000 W/m², 25 °C, AM1.5; NMOT: 800 W/m², 20 °C, AM1.5, 1 m/s Pmax +/- 3%

- & - (460S)

(NMOT)	42 ± 2 ° C
(Pmax)	-0.36%/° C
(Voc)	-0.304%/° C
(Isc)	0.050%/° C

	13	17.5
/	31	31
/	24	30
/	744	930
	2125 × 1130 × 1205	
	814	

